


COUPLEUR A CLAPET
VALVE QUICK COUPLING
ENCHUFE RAPIDO CON VALVULA

AIRMV

Mâle - Male - Macho




Code Code Código	F BSP	P MAX bar**	L	CH	kg
AIRMV04000	1/4"	300	32,5	19	0,04
AIRMV06000	3/8"	300	38,0	24	0,07
	1/2"	Voir - See - Ver: Code ABIRM08000			
AIRMV12000	3/4"	250	59,0	36	0,19
AIRMV16000	1"	200	64,1	41	0,26

COUPLEUR A CLAPET
VALVE QUICK COUPLING
ENCHUFE RAPIDO CON VALVULA

AIRFV

Femelle - Female - Hembra




Code Code Código	F BSP	P MAX bar**	L	ØD	CH	kg
AIRFV04000	1/4"	300	50,4	27	19	0,12
AIRFV06000	3/8"	300	58,3	34	24	0,22
	1/2"	Voir - See - Ver: Code ABIRF08000				
AIRFV12000	3/4"	250	90,3	48	38	0,68
AIRFV16000	1"	200	97,6	54	45	0,83

COUPLEUR A BILLE
BALL QUICK COUPLING
ENCHUFE RAPIDO CON VALVULA ESFERICA

AIRMS

Mâle - Male - Macho




Code Code Código	F BSP	P MAX bar**	L	CH	kg
AIRMS04000	1/4"	300	32,5	19	0,04
AIRMS06000	3/8"	300	38,0	24	0,08
AIRMS08000	1/2"	250	44,5	27	0,10
AIRMS12000	3/4"	250	59,0	36	0,19
AIRMS16000	1"	200	66,1	41	0,30

COUPLEUR A BILLE
BALL QUICK COUPLING
ENCHUFE RAPIDO CON VALVULA ESFERICA

AIRFS

Femelle - Female - Hembra




Code Code Código	F BSP	P MAX bar**	L	ØD	CH	kg
AIRFS04000	1/4"	300	48,9	27	19	0,11
AIRFS06000	3/8"	300	58,3	34	24	0,22
AIRFS08000	1/2"	250	63,3	38	27	0,24
AIRFS12000	3/4"	250	90,3	48	38	0,68
AIRFS16000	1"	200	99,6	54	45	0,87

COUPLEUR A CLAPET SERIE "BIR"
VALVE QUICK COUPLING - "BIR" TYPE
ENCHUFE RAPIDO CON VALVULA TIPO "BIR"

ABIRM

Mâle - Male - Macho ISO 7241-1 "A"




Code Code Código	F BSP	P MAX bar**	L	CH	kg
ABIRM04000	1/4"	350	32,0	19	0,03
ABIRM06000	3/8"	300	38,0	22	0,05
ABIRM08000	1/2"	250	44,5	27	0,08
ABIRM12000	3/4"	250	55,0	36	0,21
ABIRM16000	1"	230	63,1	41	0,28
ABIRM20000	1"1/4	230	75,0	55	0,59

COUPLEUR A CLAPET SERIE "BIR"
VALVE QUICK COUPLING - "BIR" TYPE
ENCHUFE RAPIDO CON VALVULA TIPO "BIR"

ABIRF

Femelle - Female - Hembra ISO 7241-1 "A"



Code Code Código	F BSP	P MAX bar**	L	ØD	CH	kg
ABIRF04000	1/4"	300	47,1	26	19	0,10
ABIRF06000	3/8"	300	56,1	31	22	0,14
ABIRF08000	1/2"	250	63,3	38	27	0,25
ABIRF12000	3/4"	250	82,2	48	38	0,49
ABIRF16000	1"	230	97,1	54	45	0,76
ABIRF20000	1"1/4	230	117,2	65	50	1,25


** COUPLES - COUPLED - ACOPLADO

** COUPLES - COUPLED - ACOPLADO

ABIRM

COUPLEUR "PUSH-PULL" A CLAPET
VALVE QUICK RELEASE "PUSH-PULL" COUPLING
ENCHUFE RAPIDO CON VALVULA TIPO "PUSH-PULL"

Mâle - Male - Macho




Code Code Código	F	P MAX bar**	L	CH	kg
ABIRM08000	1/2" BSP	250	44,5	27	0,08
ABIRMN0800	1/2" NPT	250	44,5	27	0,08

AIPVF

COUPLEUR "PUSH-PULL" A CLAPET
VALVE QUICK RELEASE "PUSH-PULL" COUPLING
ENCHUFE RAPIDO CON VALVULA TIPO "PUSH-PULL"

Femelle - Female - Hembra




Code Code Código	F	P MAX bar**	L	ØD	CH	kg
AIPVF08000	1/2" BSP	250	63,2	38	27	0,28
AIPVFN0800	1/2" NPT	250	63,2	38	27	0,28

AIRMS

COUPLEUR "PUSH-PULL" A BILLE
BALL QUICK RELEASE "PUSH-PULL" COUPLING
ENCHUFE RAPIDO CON VALVULA ESFERICA TIPO "PUSH-PULL"

Mâle - Male - Macho




Code Code Código	F	P MAX bar**	L	CH	kg
AIRMS08000	1/2" BSP	250	44,5	27	0,10
AIRMSN0800	1/2" NPT	250	44,5	27	0,10

AIPSF

COUPLEUR "PUSH-PULL" A BILLE
BALL QUICK RELEASE "PUSH-PULL" COUPLING
ENCHUFE RAPIDO CON VALVULA ESFERICA TIPO "PUSH-PULL"

Femelle - Female - Hembra




Code Code Código	F	P MAX bar**	L	ØD	CH	kg
AIPSF08000	1/2" BSP	250	63,2	38	27	0,29
AIPSFN0800	1/2" NPT	250	63,2	38	27	0,29

AIFIRM

COUPLEUR ANTIPOLLUTION
FLAT FACE QUICK COUPLING
ENCHUFE RAPIDO DE SUPERFICIE PLANA

Mâle - Male - Macho




Code Code Código	F BSP	SIZE	P MAX bar**	L	CH	kg
AIFIRM0400	1/4"	7	300	47,9	22	0,09
AIFIRM0600	3/8"	9	300	60,0	24	0,12
AIFIRM0800	1/2"	9	250	62,5	27	0,13
AIFIRM1200	3/4"	13	250	70,5	36	0,23
AIFIRM1600	1"	17	250	82,3	45	0,39
AIFIRM2000	1 1/4"	21	250	89,8	55	0,64

** COUPLES - COUPLED - ACOPLADO

AIFIRF

COUPLEUR ANTIPOLLUTION
FLAT FACE QUICK COUPLING
ENCHUFE RAPIDO DE SUPERFICIE PLANA

Femelle - Female - Hembra




Code Code Código	F BSP	SIZE	P MAX bar**	L	ØD	CH	kg
AIFIRF0400	1/4"	7	300	48,1	28	22	0,14
AIFIRF0600	3/8"	9	300	64,2	32	27	0,24
AIFIRF0800	1/2"	9	250	69,2	32	27	0,24
AIFIRF1200	3/4"	13	250	80,8	38	36	0,41
AIFIRF1600	1"	17	250	93,2	48	45	0,77
AIFIRF2000	1 1/4"	21	250	106,0	55	55	1,22

** COUPLES - COUPLED - ACOPLADO

COUPLEUR A CLAPET SERIE "MBV"
VALVE QUICK COUPLING - "MBV" TYPE
ENCHUFE RAPIDO CON VALVULA - TIPO "MBV"

AIM

Mâle - Male - Macho ISO 7241-A




Code Code Código	F BSP	P MAX bar**	L	CH	kg
AIM8000400	1/4"	350	35	19	0,05
AIM8000600	3/8"	315	39	22	0,06
AIM8000800	1/2"	250	46	27	0,09
AIM8001200	3/4"	250	54	34	0,19

** COUPLES - COUPLED - ACOPLADO

COUPLEUR A CLAPET SERIE "MBV"
VALVE QUICK COUPLING - "MBV" TYPE
ENCHUFE RAPIDO CON VALVULA - TIPO "MBV"

AIF

Femelle - Female - Hembra ISO 7241-A




Code Code Código	F BSP	P MAX bar**	L	ØD	CH	kg
AIF8000400	1/4"	350	47	25	19	0,08
AIF8000600	3/8"	315	58	31	24	0,15
AIF8000800	1/2"	250	67	38	30	0,27
AIF8001200	3/4"	250	81	46	38	0,47


** COUPLES - COUPLED - ACOPLADO

COUPLEUR ROTATIF EN LIGNE
IN LINE ROTARY COUPLING
ACOPLAMIENTO GIRATORIO EN LINEA

AGG



1/4" - 3/8" - 1/2" - 3/4"



1" - 1 1/4"




Code Code Código	F BSP	P MAX bar**	L	CH-CH1	kg
AGG0400000	1/4"	200	61	19/30	0,21
AGG0600000	3/8"	200	66	24/34	0,26
AGG0800000	1/2"	150	70	27/36	0,34
AGG1200000	3/4"	150	79	34/45	0,55
AGG1600000	1"	100	90	41/50	0,91
AGG2000000	1 1/4"	100	101	50/55	1,10


P MAX = pression maxi en rotation - max rotation pressure - presión max. de rotación

COUPLEUR ROTATIF A 90°
90° ROTARY COUPLING
ACOPLAMIENTO GIRATORIO A 90°

AGG90



1/4" - 3/8" - 1/2" - 3/4" - 1"



1 1/4"



Code Code Código	F BSP	P MAX bar**	L	H	CH	kg
AGG9040000	1/4"	200	69	-	19	0,31
AGG9060000	3/8"	200	78	-	24	0,42
AGG9080000	1/2"	150	86	-	27	0,52
AGG9120000	3/4"	150	99	-	34	0,90
AGG9160000	1"	100	113	-	41	1,12
AGG9200000	1 1/4"	100	120	82	50	1,75

P MAX = pression maxi en rotation - max rotation pressure - presión max. de rotación